



TZID/S Communicating AHU

Key Features:

- Communicating Wi-Fi Control
 - RS485 wire (RS485W100) connecting the indoor unit to the outdoor unit is required for full communication
- Non-Communicating 24v Control Optional
 - Installer Choice 1H/1C - 4H/2C Wiring Options
- Superior Dehumidification:
 - Slows Fan Speed When High Humidity is Detected
 - Communicating Control or 24v Thermostat w/ Dehumidification Terminal is Required
- Factory Installed / Dedicated R454B TXV
- Factory Installed Refrigerant Leak Sensor & Dissipation Board
- Compatible w/ model TZID/S Heat Pump
- High Efficiency, Variable Speed Motor to deliver consistent airflow and enhanced comfort
- Aluminum tube & fin coil construction designed for long-term reliability



Easy to Install & Service:

- 4-Way Multi Position to facilitate easy installation in tight spaces
- Flare to Braze Connections Included
- Optional Electric Heat Kits (3-25 kw)
 - AH5EH * KW

Model #	Nom Tons	CFM	Height	W x D in.	Coil Type	Cabinet	Weight
TZID18H520ZAM	1.5	618	45	17.5 x 21	A-Coil	1 PC	105.82
TZID24H520ZAM	2.0	824	45	17.5 x 21	A-Coil	1 PC	105.6
TZID30H520ZAM	2.5	1,088	49	21 x 21	A-Coil	1 PC	128.97
TZID36H520ZAM	3.0	1,188	49	21 x 21	A-Coil	1 PC	129.41
TZID48H520ZAM	4.0	1,471	53	24.5 x 21	A-Coil	1 PC	162.92
TZID60H520ZAM	5.0	1,806	53	24.5 x 21	A-Coil	1 PC	192.92